




# PRM2

## DIRECT OPERATED PRESSURE RELIEF VALVE SERIES 10

### MODULAR VERSION ISO 4401-02

**p** max 320 bar  
**Q** max 20 l/min

### MOUNTING SURFACE



### OPERATING PRINCIPLE


- The PRM2 valve is a direct operated pressure relief valve made as a modular version with mounting surface according to the ISO 4401 standards.
- It can be assembled with all ISO 4401-02 modular valves without use of pipes, using suitable tie-rods or bolts.
- It is available in versions for single relief on P or B with discharge in T, or two independent relief on A and B with discharge in T, all with three different pressure adjustment ranges.
- This valve is normally used as a hydraulic circuit pressure limiting device or as a limiting device of the pressure peaks generated during the movement of hydraulic actuators.
- It is supplied with a countersunk hex adjustment screw and locking nut.

### PERFORMANCES


(measured with mineral oil of viscosity 36cSt at 50°C)

Maximum operating pressure	bar	320
Minimum controlled pressure	see $\Delta p$ diagram.	
Maximum flow rate	l/min	20
Ambient temperature range	°C	-20 / +60
Fluid temperature range	°C	-20 / +80
Fluid viscosity range	cSt	10 ÷ 400
Fluid contamination degree	According to ISO 4406:1999 class 20/18/15	
Recommended viscosity	cSt	25
Mass: PRM2-PT and PRM2-BT PRM2-DT	kg	0.85 1

### HYDRAULIC SYMBOLS




### 1 - IDENTIFICATION CODE



### 2 - CHARACTERISTIC CURVES

(values obtained with viscosity of 36 cSt at 50°C)



### 3 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals. For fluids HFDR type (phosphate esters) use FPM seals (code V).

For the use of other kinds of fluid such as HFA, HFB, HFC, please consult our technical department.

Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics.

The fluid must be preserved in its physical and chemical characteristics.

### 4 - OVERALL AND MOUNTING DIMENSIONS

